

14M HTD Timing Pulley (Taper Lock)

Size	Z	Type	Mat	Bush	Outside Dia.	Hub Dia.	K	W	L	d3	D1	Max. Bore
28-14M-40	28	-	GG	2012	122.12	127	-	54	-	-	-	50
28-14M-55	28	-	GG	2012	122.12	127	-	70	-	-	-	50
28-14M-85	28	-	GG	2517	122.12	127	-	102	-	-	-	60
28-14M-115	28	-	GG	2517	122.12	127	-	133	-	-	-	60
29-14M-40	29	-	GG	2012	126.57	138	-	54	-	-	-	50
29-14M-55	29	-	GG	2012	126.57	138	-	70	-	-	-	50
29-14M-85	29	-	GG	2517	126.57	138	-	102	-	-	-	60
29-14M-115	29	-	GG	2517	126.57	138	-	133	-	-	-	60
30-14M-40	30	-	GG	2012	130.99	138	-	54	-	-	-	50
30-14M-55	30	-	GG	2517	130.99	138	-	70	-	-	-	60
30-14M-85	30	-	GG	2517	130.99	138	-	102	-	-	-	60
30-14M-115	30	-	GG	2517	130.99	138	-	133	-	-	-	60
32-14M-40	32	-	GG	2012	139.88	154	-	54	-	-	-	50
32-14M-55	32	-	GG	2517	139.88	154	-	70	-	-	-	60
32-14M-85	32	-	GG	2517	139.88	154	-	102	-	-	-	60
32-14M-115	32	-	GG	2517	139.88	154	-	133	-	-	-	60
34-14M-40	34	-	GG	2517	148.79	160	-	54	-	-	-	60
34-14M-55	34	-	GG	2517	146.79	160	-	70	-	-	-	60
34-14M-85	34	-	GG	2517	146.79	160	-	102	-	-	-	60
34-14M-115	34	-	GG	2517	146.79	160	-	133	-	-	-	60
36-14M-40	36	-	GG	2517	157.68	168	-	54	-	-	-	60
36-14M-55	36	-	GG	2517	157.68	168	-	70	-	-	-	60
36-14M-85	36	-	GG	3020	157.68	168	-	102	-	-	-	75
36-14M-115	36	-	GG	3020	157.68	168	-	133	-	-	-	75
38-14M-40	38	-	GG	2517	166.6	183	-	54	-	-	-	60
38-14M-55	38	-	GG	2517	166.6	183	-	70	-	-	-	60
38-14M-85	38	-	GG	3020	166.6	183	-	102	-	-	-	75
38-14M-115	38	-	GG	3020	166.6	183	-	133	-	-	-	75
40-14M-40	40	-	GG	2517	175.49	188	-	54	-	-	-	60
40-14M-55	40	-	GG	2517	175.49	188	-	70	-	-	-	60
40-14M-85	40	-	GG	3020	175.49	188	-	102	-	-	-	75
40-14M-115	40	-	GG	3020	175.49	188	-	133	-	-	-	75
44-14M-40	44	-	GG	3020	193.28	211	-	54	-	-	-	75
44-14M-55	44	-	GG	3020	293.28	211	-	70	-	-	-	75
44-14M-85	44	-	GG	3030	293.28	211	-	102	-	-	-	75
44-14M-115	44	-	GG	3030	293.28	211	-	133	-	-	-	75
48-14M-40	48	-	GG	3020	211.11	226	-	54	-	-	-	75
48-14M-55	48	-	GG	3020	211.11	226	-	70	-	-	-	75
48-14M-85	48	-	GG	3030	211.11	226	-	102	-	-	-	75
48-14M-115	48	-	GG	3030	211.11	226	-	133	-	-	-	75

"Why compete against your supplier when you can be our partner"

14M HTD Timing Pulley (Taper Lock) continued

Size	Z	Type	Mat	Bush	Outside Dia.	Hub Dia.	K	W	L	d3	D1	Max. Bore
56-14M-40	56	-	GG	3020	246.76	256	-	54	-	170	-	75
56-14M-55	56	-	GG	3020	246.76	256	-	70	-	170	-	75
56-14M-85	56	-	GG	3535	246.76	256	-	102	-	190	-	90
56-14M-115	56	-	GG	3535	246.76	256	-	133	-	-	-	90
64-14M-40	64	-	GG	3020	282.41	296	-	54	-	170	-	75
64-14M-55	64	-	GG	3020	282.41	296	-	70	-	170	-	75
64-14M-85	64	-	GG	3525	282.41	296	-	102	-	190	-	90
64-14M-115	64	-	GG	3535	282.41	296	-	133	-	190	-	90
72-14M-40	72	-	GG	3020	318.06	-	-	54	-	170	-	75
72-14M-55	72	-	GG	3020	318.06	-	-	70	-	170	-	75
72-14M-85	72	-	GG	3535	318.06	-	-	102	-	190	-	90
72-14M-115	72	-	GG	3535	318.06	-	-	133	-	190	-	90
80-14M-40	80	-	GG	3535	353.71	-	-	133	-	190	-	90
80-14M-55	80	-	GG	3020	353.71	-	-	70	-	170	-	75
80-14M-85	80	-	GG	3525	353.71	-	-	102	-	190	-	90
80-14M-115	80	-	GG	3535	353.71	-	-	133	-	190	-	90
90-14M-40	90	-	GG	3020	398.28	-	-	54	-	170	-	75
90-14M-55	90	-	GG	3020	398.28	-	-	70	-	170	-	75
90-14M-85	90	-	GG	3525	398.28	-	-	102	-	190	-	90
90-14M-115	90	-	GG	3535	398.28	-	-	133	-	190	-	90
112-14M-40	112	-	GG	3020	496.32	-	-	54	-	170	-	75
112-14M-55	112	-	GG	3020	496.32	-	-	70	-	170	-	75
112-14M-85	112	-	GG	3525	496.32	-	-	70	-	170	-	75
112-14M-115	112	-	GG	3535	496.32	-	-	133	-	190	-	90
144-14M-40	144	-	GG	3020	638.92	-	-	54	-	170	-	75
144-14M-55	144	-	GG	3020	638.92	-	-	70	-	170	-	75
144-14M-85	144	-	GG	3535	638.92	-	-	102	-	190	-	90
144-14M-115	144	-	GG	4040	638.92	-	-	133	-	230	-	100
168-14M-40	168	-	GG	3020	745.87	-	-	54	-	170	-	75
168-14M-55	168	-	GG	3020	745.87	-	-	70	-	170	-	75
168-14M-85	168	-	GG	3525	745.87	-	-	102	-	190	-	90
168-14M-115	168	-	GG	4040	745.87	-	-	133	-	230	-	100
192-14M-40	192	-	GG	3020	852.82	-	-	54	-	170	-	75
192-14M-55	192	-	GG	3020	852.82	-	-	70	-	170	-	75
192-14M-85	192	-	GG	4040	852.82	-	-	102	-	230	-	100
192-14M-115	192	-	GG	4040	852.82	-	-	133	-	230	-	100
216-14M-40	216	-	GG	3020	959.76	-	-	54	-	170	-	75
216-14M-55	216	-	GG	3535	959.76	-	-	-	-	-	-	-
216-14M-85	216	-	GG	4040	959.76	-	-	102	-	230	-	100
216-14M-115	216	-	GG	4040	959.76	-	-	133	-	230	-	100

"Why compete against your supplier when you can be our partner"

Finer Power Transmissions carries a large range of Taper Locked, HTD Timing Pulley's in 8M and 14M pitch.

Timing Pulleys are measured by:

38	8M	50
Teeth	Pitch	Width

