



CODE	SIZE (in)	PITCH (is)	SWL (T)	Wt. (kg)	DIMENSIONS (mm)					
					D	D1	D2	H	H1	W
604005	3/8"	0.0625	0.3	0.07	10	14	22	35	18	32
604010	1/2"	0.0833	0.5	0.16	12	19	28	45	23	42
604015	5/8"	0.0909	0.9	0.313	16	24	36	59	30	53
604020	3/4"	0.1	1.4	0.525	20	28	44	69	37	62
604025	7/8"	0.125	2.0	0.825	22	33	50	81	42	72
604030	1"	0.1429	2.8	1.25	24	37	58	91	47	82
604035	1 1/4"	0.1429	4.6	2.03	32	48	72	115	62	104

WORKING LOAD LIMIT FOR BS TYPE EYE BOLTS (T)							
METRIC	IMPERIAL	AXIAL	SIDE 90°	VERTICAL PAIR	30° ANGLE	60° ANGLE	90° ANGLE
M10	3/8"	0.25	0.06	0.12	0.31	0.2	0.12
M12	1/2"	0.4	0.1	0.2	0.5	0.32	0.2
M16	5/8"	0.8	0.2	0.4	1.0	0.64	0.4
M20	3/4"	1.6	0.4	0.8	2.0	1.28	0.8
M22	7/8"	2.0	0.5	1.0	2.5	1.6	1.0
M24	1"	2.5	0.62	1.25	3.1	2.0	1.25
M30	1-1/8"	4.0	1.0	2.0	5.0	3.2	2.0
M33	1-1/4"	5.0	1.25	2.5	6.3	4.0	2.5
M36	1-1/2"	6.3	1.57	3.1	7.9	5.0	3.1
M39	1-9/16"	7.0	1.75	3.5	8.8	5.6	3.5
M42	1-5/8"	8.0	2.0	4.0	10.0	6.4	4.0
M48	2"	10.0	2.5	5.0	12.6	8.0	5.0
M56	2-1/4"	15.0	3.7	7.5	18.9	12.0	7.5