









RIBBED BELTS

PIX-X'ceed® INDUSTRIAL POLY V-BELTS

					
PH	2.9	1.60	13	280 mm	5080 mm
PJ	3.8	2.34	20	280 mm	5080 mm
PK	4.5	3.56	50	280 mm	5080 mm
PL	7.6	4.70	75	280 mm	5080 mm
PM	13.3	9.40	180	280 mm	5080 mm

PIX-X'ceed® DS DOUBLE SIDED POLY V-BELTS

			
DPK	2 to 13 ribs		1195 mm
DPL	2 to 11 ribs		3105 mm

PIX-X'ceed® EL ELASTICATED POLY V-BELT(PJ)

EL nPJ	2 to 20	600 mm	3105 mm
--------	---------	--------	---------

Note: n = no. of ribs

PIX-X'ceed® HT EPDM POLY V-BELTS

Features:







- Working Temperature up to 130°C.
- Abrasion & Flex cracking resistance is very high.
- Longer service life as compared to regular belts.
- Good dimensional stability.
- Higher power transmission.

Applications:

Automobiles, High Speed Engines.

SPECIAL CONSTRUCTION BELTS

PIX-X'set® PT-0

						
B (17x14)	17 mm	14 mm	3 mm	85"	658"	Li
B (17x16)	17 mm	16 mm	5 mm	85"	658"	Li
A (13x13)	13 mm	13 mm	5 mm	48"	257"	Li
37 x 25	37 mm	25 mm	5 mm	4064 mm	16713 mm	Lp

PIX-X'set® PT-HC HONEY COMB BELTS

B (17x17)	17 mm	17 mm	6 mm	32"	658"	Li
C (22x20)	22 mm	20 mm	6 mm	38"	658"	Li









PIX-X'set® PT-6

B (17x22)	17 mm	22 mm	11 mm	85"	375"	Li
B (17x26)	17 mm	26 mm	15 mm	66"	375"	Li
B (17x21)	17 mm	21 mm	10 mm	42"	79"	Li
C (22x25)	22 mm	25 mm	11 mm	73"	350"	Li

PIX-X'set® PT-7

37(37x25)	37 mm	25 mm	7 mm	4064 mm	8890 mm	Lp
D (32x26)	32 mm	26 mm	7 mm	142"	633"	Li

PIX-X'set® DS HEXAGONAL BELTS

								
AA	13.0 mm	10.0 mm	40	IS 11038, ISO 5289	80 mm	43"	260"	Li
BB	17.0 mm	14.0 mm	40	IS 11038, ISO 5289	125 mm	40"	660"	Li
CC	22.0 mm	17.0 mm	40	IS 11038, ISO 5289	224 mm	73"	658"	Li
25	25.0 mm	22.0 mm	40	RMA IP 21, IS 11038, ISO 5289	280 mm	89"	681"	Le