

## **TECHNICAL DATA SHEET**

### A NEW FORCE IN CHEMICAL MANUFACTURING

AEROSOLS | WELDING CHEMICALS | ADHESIVES & THREADLOCKERS | ANTI-SEIZE & GREASES | CLEANING CHEMICALS & SOLVENTS | ELECTRICAL & ELECTRONICS

Issued: June 2019

### **Cable Lubricant**

PART NUMBER	AVAILABLE SIZE
CT-CPL-1L	1L Bottle
CT-CPL-5L	5L Bucket
CT-CPL-20L	20L Bucket

### **PRODUCT DESCRIPTION**

Chemtools<sup>®</sup> Cable Lubricant maximises the efficiency of wire and cable pulling and hauling by reducing friction and increasing the ease of passage through horizontal and vertical piping, ducts, and conduits. It is a nonconductive, non-combustible, and temperature stable gel which is slow to dry and provides excellent cling for easy hand application.

Cable Lubricant is extremely clean and odourless, non-toxic, non-staining, and washes easily away. It is compatible with most cable jackets and ideal for electrical, communication, and data installation, from simple upgrade wiring to full indoor construction.

### APPLICATION

Apply lubricant generously to the head of the wires feeding into the pipe and a few feet down the length of the wire. Lubricate the conduit itself if required.

Continue to apply lubricant to the wires just prior to entering the conduit and as they are being fed, pulled, or hauled through.

### STORAGE

Store in a cool, dry place, in tightly closed original containers, at a room temperature between 5°C to 40°C. Do not place in direct sunlight or near any heat source. Do not return any used material to its original container.

TECHNICAL DATA			
<b>PHYSICAL PROPERTIES:</b> Appearance Odour Specific Gravity @ 25°C Purity Temperature Range		Translucent Blue Gel Odourless 1.2 98% -5°C to +50°C	R
Technical Data Sheet:	Cable Lubricant		Page 1 of 2

TECHNICAL DATA SHEET BY CHEMTOOLS PTY LTD (ABN 12 114 400 083) • HEAD OFFICE/MANUFACTURING FACILITY: UNIT 2, 14 - 16 LEE HOLM ROAD ST MARYS NSW 2760 VISIT US ONLINE: WWW.CHEMTOOLS.COM.AU • PHONE: 1300 738 250 | INTERNATIONAL PHONE: +61 2 9833 9766 • AUSTRALIAN OWNED & OPERATED • GLOBALLY UNSURPASSED QUALITY



# **TECHNICAL DATA SHEET**

## A NEW FORCE IN CHEMICAL MANUFACTURING Aerosols | welding chemicals | adhesives & threadlockers | anti-seize & greases | cleaning chemicals & solvents | electrical & electronics

### **FIRST AID & SAFETY PRECAUTIONS**

Please refer to Safety Data Sheet (SDS) before use. Use with adequate ventilation and avoid breathing fumes. Avoid contact with eyes and skin. This product may produce adverse health conditions, ranging from minor skin irritation to serious systemic effects. It should not be used, stored, or transported until the handling precautions and recommendations as stated in the Safety Data Sheet (SDS) for this product have been fully understood by all persons who will work with the material.

### DISCLAIMER

Chemtools® has made every effort to ensure the information provided in this Technical Data Sheet is accurate at the time of publication. Chemtools® expressly recommends that the user make his/her own assessment to determine the suitability of the product for its intended purpose prior to application. Chemtools shall not be responsible for loss, damage, or injury, resulting from the reliance upon, or failure to adhere to, any recommendations or information contained herein; nor from abnormal use of the material; nor from any hazard inherent in the nature of the material.

### FURTHER INFORMATION

Please visit Chemtools® online at www.chemtools.com.au for product photos, marketing materials, Technical Data Sheets, Safety Data Sheets, contact details, and other company/business related information.

**Technical Data Sheet: Cable Lubricant**  Page 2 of 2

TECHNICAL DATA SHEET BY CHEMTOOLS PTY LTD (ABN 12 114 400 083) • HEAD OFFICE/MANUFACTURING FACILITY: UNIT 2, 14 - 16 LEE HOLM ROAD ST MARYS NSW 2760 VISIT US ONLINE: WWW.CHEMTOOLS.COM.AU • PHONE: 1300 738 250 | INTERNATIONAL PHONE: +61 2 9833 9766 • AUSTRALIAN OWNED & OPERATED • GLOBALLY UNSURPASSED QUALITY