



NA2 Series

Part No.	Basic Dimensions (mm)										Basic Loads (KN)		N.W. (kg)
	d	D	B	C	S	a	b	P	G	h	Cr	Cor	
PFB_NA204	20	47	43.5	34.0	16	17.0	33.3	13.5	4.0	5.0	11.01	5.68	0.22
PFB_NA205	25	52	44.3	34.8	17	17.4	38.1	13.5	4.2	5.0	12.04	6.71	0.25
PFB_NA206	30	62	48.3	36.4	19	18.2	44.5	15.9	4.8	6.0	16.68	9.63	0.41
PFB_NA207	35	72	51.1	37.6	20	18.8	55.6	17.5	5.4	6.5	22.02	13.07	0.60
PFB_NA208	40	80	56.3	42.8	21	21.4	60.3	18.3	5.9	6.5	28.04	17.03	0.78
PFB_NA209	45	85	56.3	42.8	22	21.4	63.5	18.3	6.1	6.5	28.12	17.54	0.85
PFB_NA210	50	90	62.7	49.2	24	24.6	69.9	18.3	6.5	6.5	30.10	19.87	1.01
PFB_NA211	55	100	71.4	55.4	25	27.7	76.2	20.7	7.1	8.0	37.24	25.11	1.39
PFB_NA204-12	0.750	1.850	1.713	1.339	0.630	0.669	1.311	0.532	0.158	0.197	11.01	5.68	0.48
PFB_NA205-16	1.000	2.047	1.744	1.370	0.669	0.685	1.500	0.532	0.165	0.197	12.04	6.71	0.55
PFB_NA206-20	1.250	2.441	1.902	1.433	0.748	0.717	1.752	0.626	0.189	0.236	16.68	9.63	0.90
PFB_NA207-20	1.250	2.835	2.012	1.480	0.787	0.740	2.189	0.689	0.213	0.256	22.02	13.07	1.32
PFB_NA207-23	1.438	2.835	2.012	1.480	0.787	0.740	2.189	0.689	0.213	0.256	22.02	13.07	1.32
PFB_NA208-24	1.500	3.150	2.217	1.685	0.827	0.843	2.374	0.721	0.232	0.2	28.04	17.03	1.72
PFB_NA209-28	1.750	3.346	2.217	1.685	0.866	0.843	2.500	0.721	0.240	0.256	28.12	17.54	1.87
PFB_NA210-30	1.625	3.543	2.469	1.937	0.945	0.969	2.752	0.721	0.256	0.256	30.10	19.87	2.22
PFB_NA211-32	2.000	3.937	2.811	2.181	0.984	1.091	3.000	0.815	0.280	0.315	37.24	25.11	3.16

