


2

INSERT BALL BEARINGS

UK3 Series heavy duty

Adapter sleeve locking, spherical outer ring



SHAFT DIA. d		BEARING No.	DIMENSIONS mm				BASIC LOAD RATING kN		LIMITING SPEED RPM	MASS Kg	ADAPTER SLEEVE No.
(mm)	(in)		D1	D	B1	BE	DYN C	STATIC Co			
20	³ / ₄	UK305	25	62	26	20	21.2	10.9	5200	0.36	HE2305 H2305
25	⁷ / ₈ 1	UK306	30	72	29	23	26.7	15.0	4300	0.59	HS2306 H2306 HE2306
30	¹ / ₈	UK307	35	80	33	25	33.5	19.1	3900	0.75	HS2307 H2307
35	¹ / ₄ ¹ / ₈	UK308	40	90	34	27	40.5	24.0	3400	1.02	HE2308 HS2308 H2308
40	¹ / ₁₆ ¹ / ₂	UK309	45	100	37	29	53.0	32.0	3000	1.38	HA2309 HE2309 H2309
45	¹ / ₈ ¹ / ₁₆ ¹ / ₄	UK310	50	110	41	32	62.0	38.5	2700	1.68	HS2310 HA2310 HE2310 H2310
50	¹ / ₈ ¹ / ₁₆ 2	UK311	55	120	44	34	71.5	45.0	2500	2.06	HS2311 HA2311 H2311 HE2311
55	² / ₈	UK312	60	130	47	36	82.0	52.0	2300	2.53	HS2312 H2312
60	² / ₁₆ ² / ₄ ² / ₈	UK313	65	140	49	39	92.5	60.0	2200	3.08	HA2313 HE2313 H2313 HS2313
65	² / ₁₆ ² / ₂ ² / ₈	UK315	75	160	55	43	113.0	77.0	1900	4.84	HA2315 HE2315 H2315 HS2315
70	² / ₁₆ ² / ₄	UK316	80	170	58	45	123.0	86.5	1800	5.75	HA2316 HE2316 H2316
75	² / ₁₆ 3	UK317	85	180	60	47	133.0	97.0	1700	6.72	H2317 HA2317 HE2317
80	-	UK318	90	190	64	49	143.0	107.0	1600	7.87	H2318
85	³ / ₄	UK319	95	200	67	51	153.0	119.0	1500	9.02	HE2319 H2319
90	³ / ₂	UK320	100	215	73	55	173.0	141.0	1400	11.1	HE2320 H2320
100	-	UK322	110	240	80	59	205.0	179.0	1300	14.9	H2322
110	-	UK324	120	260	86	63	207.0	185.0	1200	18.0	H2324
115	-	UK326	130	280	90	67	229.0	214.0	1000	23.3	H2326
125	-	UK328	140	300	95	71	253.0	246.0	1000	28.9	H2328